

Serial No. 10/761,047

Docket No. 200313631-1

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A system comprising:
a first node that provides a broadcast request for data, the first node receiving a read conflict response to the broadcast request from the first node, the read conflict response indicating that a second node has a pending broadcast read request for the data; and
a third node that provides the requested data to the first node in response to the broadcast request from the first node, the first node filling the data provided by the third node in a cache associated with the first node.
2. (Original) The system of claim 1, wherein the broadcast request provided by the first node is a source broadcast read request.
3. (Original) The system of claim 2, wherein the first node provides a read conflict response to the broadcast read request from the second node, the read conflict response provided by the first node indicating that the broadcast read request of the first node conflicts with the pending broadcast read request of the second node.
4. (Original) The system of claim 3, wherein the third node provides the requested data to the second node in response to the broadcast read request from the second node, the second node filling the data provided by the third node in a cache associated with the second node.
5. (Original) The system of claim 1, wherein the request for data broadcast by the first node is a source broadcast write request.
6. (Original) The system of claim 5, wherein the first node provides a second conflict response to the pending broadcast read request from the second node, the second conflict response provided by the first node indicating that the write request broadcast by the first node conflicts with the broadcast read request from the second node.

Serial No. 10/761,047**Docket No. 200313631-1**

7. (Original) The system of claim 6, wherein the broadcast request provided by the first node is broadcast using a first cache coherency protocol, the second node in response to the second conflict response provided by the first node reissues the pending broadcast read request of the second node.
8. (Original) The system of claim 7, wherein the first cache coherency protocol is a source broadcast cache coherency protocol and the second node reissues the broadcast read request using a forward progress cache coherency protocol.
9. (Original) The system of claim 6, wherein the third node provides the requested data to the second node in response to the pending broadcast read request of the second node, the second conflict response provided by the first node preventing the second node from filling the data provided by the third node in a cache associated with the second node.
10. (Original) The system of claim 6, wherein the third node provides shared data to the second node in response to the pending broadcast read request of the second node, the second node filling a cache associated with the second node with the shared data and associating an invalid state with the shared data filled in the cache associated with the second node.
11. (Original) The system of claim 1, wherein the third node comprises one of a home node and an owner node.
12. (Original) The system of claim 1, wherein the broadcast request provided by the first node is broadcast using a source broadcast cache coherency protocol.
13. (Original) The system of claim 1, wherein the first node defines a first processor and the second node defines a second processor, the first and second processors having an associated cache, the associated caches of the first and second processors each comprising a plurality of cache lines, each cache line having a respective tag address that identifies associated data and each cache line having state information that indicates a state of the associated data for the respective cache line, the first and second processors being capable of communicating with each other and with other nodes of the system through an interconnect.

Serial No. 10/761,047**Docket No. 200313631-1**

14. (Original) The system of claim 13, further comprising a first cache controller associated with the first processor and a second cache controller associated with the second processor, the first cache controller being operative to manage data requests and responses for the associated cache of the first processor, the first cache controller effecting state transitions associated with the data in the associated cache of the first processor based on the data requests and responses for the associated cache of the first processor, the second cache controller being operative to manage data requests and responses for the associated cache of the second processor, the second cache controller effecting state transitions associated with the data in the associated cache of the second processor based on the data requests and responses for the associated cache of the second processor.

15. (Original) The system of claim 13, wherein the system implements a hybrid cache coherency protocol wherein each of the first, second, and third processors employs a source broadcast-based protocol to issue a request for the data and provide responses for the data, and employs an associated second protocol to reissue a request for the data in response to the request failing in the source broadcast protocol, the second protocol employing a forward progress technique.

16. (Original) A multi-processor network comprising:
a first processor node operative to issue a first source broadcast request for data;
a second processor node operative to issue a second source broadcast request for the data;
and
a third node operative to provide a data response in response to the respective source broadcast requests of the first and second processor nodes, the third node being one of an owner processor node and a memory node;
the second processor node being operative to provide a read conflict response to the first source broadcast request when the second source broadcast request is a read request, the second processor node being operative to provide a second conflict response to the first source broadcast request when the second source broadcast request is a write request;
the first processor node being operative in response to receiving a read conflict response from the second processor to implement a cache fill with the data provided by the third node.

Serial No. 10/761,047**Docket No. 200313631-1**

17. (Original) The multi-processor network of claim 16, wherein the first processor node is operative in response to a write conflict response from the second processor node to issue a request for the data using a forward progress technique.
18. (Original) The multi-processor network of claim 17, wherein the second conflict response from the second processor node prevents the first processor node from implementing the cache fill with the data provided by the third node.
19. (Original) The multi-processor network of claim 16, wherein the first source broadcast request is one of a source broadcast write request and a source broadcast read request.
20. (Original) The multi-processor network of claim 16, wherein the source broadcast request issued by the first processor node exists concurrently with the source broadcast request issued by the second processor node.
21. (Original) The multi-processor network of claim 16, wherein the third processor node provides shared data to the second processor node in response to the second processor node providing the second source broadcast request as a broadcast read request, the second processor node filling the shared data in a cache associated with the second processor node and associating an invalid state with the data in the cache associated with the second processor node.
22. (Original) The multi-processor network of claim 16, wherein each of the first, second, and third processor nodes has an associated cache that comprises a plurality of cache lines, each cache line having a respective tag address that identifies associated data and having state information that indicates a state of the associated data for the respective cache line, the first, second, and third processor nodes being capable of communicating with each other and with other nodes of the system through an interconnect, the multi-processor network further comprising a first cache controller associated with the first processor node, a second cache controller associated with the second processor node, and a third cache controller associated with the third processor node, the first cache controller being operative to manage data requests and responses for the associated cache of the first processor, the first cache controller effecting state transitions associated with the data in the associated cache of the first processor based on the data requests and responses for the associated cache of the first processor, the second cache controller

Serial No. 10/761,047

Docket No. 200313631-1

being operative to manage data requests and responses for the associated cache of the second processor, the second cache controller effecting state transitions associated with the data in the associated cache of the second processor based on the data requests and responses for the associated cache of the second processor, the third cache controller being operative to manage data requests and responses for the associated cache of the third processor, the third cache controller effecting state transitions associated with the data in the associated cache of the third processor based on the data requests and responses for the associated cache of the third processor.

23. (Original) The multi-processor network of claim 16, wherein the network implements a hybrid cache coherency protocol in which each of the first, second, and third processor nodes employs a source broadcast-based protocol to issue requests for data and provide responses to requests, and employs an associated protocol employing a forward progress technique to reissue a request for data in response to a request failing in the source broadcast protocol.

24. (Original) A computer system comprising:

a first processor operative to issue a source broadcast request for data;

a second processor operative to issue a source broadcast request for the data; and

a third processor operative to provide a data response to both the first and second processors in response to the source broadcast requests of the first and second processors;

the second processor in response to the source broadcast request of the first processor providing a read conflict response when the source broadcast request of the second processor is a source broadcast read request, the second processor in response to the source broadcast request of the first processor providing a second conflict response when the source broadcast request of the second processor is a source broadcast write request; and

the first processor in response to the read conflict response of the second processor being operative to fill the data provided by the third processor in a cache associated with the first processor.

25. (Original) The computer system of claim 24, wherein the first processor in response to the second conflict response of the second processor is operative to reissue the source broadcast

Serial No. 10/761,047**Docket No. 200313631-1**

request from the first processor by issuing a request for the data employing a forward progress protocol.

26. (Original) The computer system of claim 24, wherein the second conflict response from the second processor prevents the first processor from filling the data provided by the third processor in the cache associated with the first processor.

27. (Original) The computer system of claim 24, wherein the third processor provides a shared data response to the first processor in response to the source broadcast request for the data, the first processor being operative to place the shared data in the cache associated with the first processor and associate an invalid state with the data in the cache associated with the first processor.

28. (Original) The computer system of claim 24, wherein the computer system implements hybrid cache coherency protocol in which each of the first, second, and third processor employs a source broadcast-based protocol to issue requests for data and provide responses to requests, and employs an associated protocol employing a forward progress technique to reissue a request for data in response to a request failing in the source broadcast protocol.

29. (Original) A system comprising:

means for providing a broadcast request for data from a first node using a first cache coherency protocol;

means for providing a read conflict response from a second node to the broadcast request from the first node when the second node has a pending broadcast read request for the data;

means for providing the data from a third node to the first node in response to the broadcast request from the first node; and

means for placing the data from the third node in a cache associated with the first node in response to the read conflict response from the second node.

Serial No. 10/761,047

Docket No. 200313631-1

30. (Original) The system of claim 29, wherein the means for providing a broadcast request from the first node comprises means for providing a broadcast read request for the data from the first node, the system further comprising:

means for providing a read conflict response from the first node to the second node in response to the broadcast read request of the second node, the read conflict response from the first node indicating that the pending broadcast read request of the second node conflicts with the broadcast read request for the data from the first node;

means for providing the requested data to the second node from the third node in response to the broadcast read request of the second node; and

means for filling the data provided to the second node by the third node in a cache associated with the second node in response to the second node receiving the read conflict response from the first node.

31. (Original) The system of claim 29, wherein the means providing a broadcast request from the first node comprises means for providing a broadcast write request for the data from the first node, the system further comprising:

means for providing a second conflict response from the first node to the second node in response to the pending broadcast read request of the second node, the second conflict response from the first node indicating that the pending broadcast read request of the second node conflicts with the broadcast write request for the data from the first node; and

means for reissuing the broadcast read request of the second node employing a forward progress protocol in response to the second conflict response provided by the first node.

32. (Original) The system of claim 31, further comprising means for preventing the second node from placing the data provided by the third node in a cache associated with the second node in response to the second conflict response provided by the first node.

33. (Original) The system of claim 29, wherein the means for providing the data from the third node to the first node is operative to provide shared data to the first processor, the means for placing the data provided by the third node placing the shared data in the cache associated with the first processor, the system further comprising means for associating an invalid state with the data in the cache associated with the first processor.

Serial No. 10/761,047

Docket No. 200313631-1

34. (Original) A method comprising:
- providing a source broadcast request from a first node for data;
 - providing a read conflict response to the first node from a second node in response to the source broadcast request from the first node, the read conflict response indicating that the second node has a pending broadcast read request for the data;
 - providing the requested data to the first node from a third node in response to the source broadcast request from the first node; and
 - placing the data provided by the third node in a cache associated with the first node.
35. (Original) The method of claim 34, wherein providing a source broadcast request from the first node comprises providing a source broadcast read request from the first node, the method further comprising:
- providing a read conflict response from the first node to the second node in response to the pending broadcast read request of the second node, the read conflict response from the first node indicating that the pending broadcast read request of the second node conflicts with the source broadcast read request provided by the first node;
 - providing the requested data to the second node from the third node in response to the pending broadcast read request of the second node; and
 - placing the data provided to the second node by the third node in a cache associated with the second node.
36. (Original) The method of claim 34, wherein providing a broadcast request from the first node comprises providing a broadcast write request from the first node, the method further comprising:
- providing a second conflict response from the first node to the second node in response to the pending broadcast read request of the second node, the second conflict response from the first node indicating that the pending broadcast read request of the second node conflicts with the broadcast write request provided by the first node; and
 - preventing placement of the data in a cache associated with the second node in response to the second conflict response provided by the first node.

Serial No. 10/761,047**Docket No. 200313631-1**

37. (Original) The method of claim 36, further comprising reissuing the source broadcast read request of the second node as a forward progress protocol read request for the data from the second node in response to the second conflict response provided by the first node

38. (Original) A computer system comprising a hybrid cache coherency protocol that employs source broadcast protocol mode and a forward progress protocol mode, the computer system being operative to fill a cache line associated with a source node with requested data provided in response to a source broadcast protocol mode request for the data when there is a source broadcast protocol read conflict with another node in the computer system, the computer system being further operative to reissue a request for the data from a source node using a forward progress protocol mode request for the data when there is a source broadcast protocol second conflict with another node in the computer system.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.